COAPS

Commander Open Architecture Panoramic Sight

COAPS is an advanced, modular dual-axis stabilized sight for MBTs and AFVs. Based on open architecture, it is easily adaptable to sensor additions and changes.

Main Advantages & Features

- Facilitates long-range target acquisition day and night, in both stationary and mobile situations
- Wide-range of advanced sensors, including 3-5µm or 8-12µm thermal imagers, color zoom camera and eyesafe laser range finder (ELRF), as well as:
  - Built-in electronic unit
  - Independently stabilized dual-axis
  - Dedicated ballistic protection
- Independent 360º panoramic view
- Provides hunter-killer capabilities with the turret system through the existing GMS

Applications

- Fire control computation
- Long-range target acquisition
- Independent surveillance

Elbit Systems™
ISTAR & EW

COAPS

Commander Open Architecture Panoramic Sight

Technical Data

Sight

• Line of sight freedom	El: -20º to +60º Az: n x 360º
• Stabilization accuracy	Better than 100 µrad (1ə)
• Positioning/slaving accuracy	Better than 150 µrad (1ə)
• Tracking speed	
• -E- l, Az	0,2 mil/s to 800 mil/s
• -E- l acceleration	3 Rad/s2
• -A- z acceleration	1 Rad/s2

Sensors

FLIR

	Option 1	Option 2
• Spectral waveband	3-5 µm	8-12µm
• Detector	640 x 512 / 1024 x 768	640 x 512 / 1280 x 1024
• Video output	CCIR-B or digital 10 bit format	CCIR-B or digital 10 bit format
• FOVs	Continuous optical zoom 1.7º-25º	NFOV: 3.2º(H) x 2.4º(V) WFOV: 9.6º(H) x 7.2º(V)
• Range performance (km) NFOV NATO target	10.5/4.5/2.2 (DRI)	10.5/4.5/2.2 (DRI)

Day Channel Camera	
• Wavelength	Visible range
• Technology	CCD / CMOS HDTV
• Sensitivity	Color mode: 12 Lux Black & white mode: 2 Lux
• Video output	CCIR-B/PAL
• FOV	Continuous optical zoom x21 NFOV: 1.7º x 1.3º
• Range performance (km) NFOV NATO target	11.5/5.1/2.3 (DRI)

ELRF	
• Wavelength	1.54µm (eyesafe)
• Range	200 to 7000 ± 5 m for NATO size target 2.3 x 2.3
• Discrimination between targets	5 mrad, 30 m
• Pulse repetetion rate	10 ppm

Environmental conditions

• Operating temperature	-20ºC to +55ºC
• Storage temperature	-30ºC to +70ºC
• Vibration	MIL-STD-810E, Method 514.4

Elbit Systems Ltd.
Advanced Technology Center, P.O.B 539, Haifa 3100401, Israel
E-mail: istar@elbitsystems.com www.elbitsystems.com

Follow us on

The logo brand, product, service and process names appearing herein are the trademarks or service marks of Elbit Systems Ltd. its affiliated companies or, where applicable, of other respective holders.
All information in this document is for general information only, and is subject for change without notice. © 2016. This brochure contains Elbit Systems and others proprietary information. EP2.3-MKT-039